

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A method for the detection of an object moving in the monitored region of a camera, wherein

- an actual image of the monitored region is recorded by the camera;
- at least one actual measured value is derived from the actually recorded image which provides information on differences between at least two different image regions and which is invariant with respect to image displacements, image rotations and/or image size changes;
- this actual measured value is compared with a corresponding reference value derived from a stored reference image recorded by the camera; and
- an object recognition reaction is triggered on a pre-set deviation of the actual measured value from the reference value;
- a structure, which is a component of the image, is superimposed on the reference image and the actually recorded image, the reference value and a measured value being gained from the corresponding structure information; and
- a check is made whether the camera is in working order by recording images regularly with and without a structure generated in the monitored region and by checking whether the structure information is found with a generated structure and is not found with no structure generated.

Claim 2 (currently amended): A method in accordance with claim [[1]] 16, characterized in that a structure, which is a component of the image, is superimposed on the reference image and the actually recorded image; and in that the reference value and a measured value are gained from the corresponding structure information.

Claim 3 (currently amended): A method in accordance with claim [[2]] 1, characterized in that the structure in the monitored region is generated during the recording of

the reference image and of the actual images of the monitored region by means of a projection device and/or by means of a moved light beam.

Claim 4 (currently amended): A method in accordance with claim ~~[[2]]~~ 1, characterized in that mutually different structures are generated in the monitored region simultaneously or in time sequence.

Claim 5 (previously presented): A method in accordance with claim 4, characterized in that different projection devices are used for the generation of the different structures.

Claim 6 (previously presented): A method in accordance with claim 1, characterized in that an image of an object-free monitored region is used as the reference image.

Claim 7 (original): A method in accordance with claim 1, characterized in that a reaction is triggered when the comparison of the actual measured value with the reference value provides a comparison value which lies outside a pre-set tolerance range.

Claim 8 (previously presented): A method in accordance with claim 1, characterized in that the image information or structure information comprises, among other things, information related to reference points, with the reference points in particular marking the boundaries of the monitored region.

Claim 9 (previously presented): A method in accordance with claim 8, characterized in that reflectors are used for the marking of the reference points and are arranged at invariant positions relative to the monitored region.

Claim 10 (original): A method in accordance with claim 1, characterized in that a plurality of actual measured values of the same or of a different type is derived from the actual image information or structure information and is compared with corresponding stored reference values derived from the image information or the structure information of the reference image.

Claim 11 (original): A method in accordance with claim 1, characterized in that the measured value(s) or reference value(s) include one or more pieces of the following information:

- distance between two different image regions or structure regions or between a reference point and an image region or a structure region;
- brightness difference between two different image regions or structure regions or between a reference point and an image region or a structure region;
- color difference between two different image regions or structure regions or between a reference point and an image region or a structure region;
- brightness gradient between two different image regions or structure regions or between a reference point and an image region or a structure region.

Claim 12 (previously presented): A method in accordance with claim 1, characterized in that a correlation function is calculated between at least one region of the actual image information or structure information and a corresponding region of the image information or of the structure information of the reference image, and the shape of this correlation function and/or determined values of this correlation function are used for the decision with respect to the triggering of an object recognition reaction.

Claim 13 (previously presented): A method in accordance with claim 1, characterized in that the monitored region is illuminated by means of at least one light source during the recording of the reference image and of the actual images of the monitored region.

Claim 14 (currently amended): A method in accordance with claim ~~[[2]]~~ 16, characterized in that a check is made whether the camera is in working order by recording images regularly with and without a structure generated in the monitored region and by checking whether the structure information is found with a generated structure and is not found with no structure generated.

Claim 15 (previously presented): A method in accordance with claim 14, characterized in that mutually different structures, which are generated simultaneously or in time sequence in the monitored region, are used for the checking of the camera.

Claim 16 (currently amended): ~~A method in accordance with claim 1,~~
~~characterized in that~~ A method for the detection of an object moving in the monitored region of a camera, wherein

- an actual image of the monitored region is recorded by the camera;
- at least one actual measured value is derived from the actually recorded image which provides information on differences between at least two different image regions and which is invariant with respect to image displacements, image rotations and/or image size changes;
- this actual measured value is compared with a corresponding reference value derived from a stored reference image recorded by the camera;
- an object recognition reaction is triggered on a pre-set deviation of the actual measured value from the reference value; and
- one image is always recorded per shot with a generated structure and one with no structure generated, both in the recording of reference images and in the recording of actual images, and subsequently only the difference image from these two images is further processed.

Claim 17 (original): A method in accordance with claim 16, characterized in that an objection recognition reaction or a malfunction reaction is always triggered when a difference results between the reference difference image and an actually recorded difference image.

Claims 18-22 (cancelled)